

# LIGHTING

## LED FLOODLIGHTS



### VELOCITY SERIES

Designed for performance, reliability and ease of installation, the Velocity Floodlight is the perfect option for commercial applications. Its high efficacy delivers optimum performance, complemented by a diffused lens and adjustable bracket which enables easy installation across a range of applications.

With an IP66 rating and tolerance across a wide ambient temperature range, the Velocity Series is built to last.

### FEATURES

- User friendly driver compartment and large 6mm terminal block
- 2x25mm and 2x20mm conduit entries
- Ease of installation (no bracket removal required and hinge lid to terminal block)
- Supply is cut-off to driver when lid is opened
- High efficacy
- IP66 rating

### SPECIFICATIONS

POWER FACTOR	>0.98	<b>MODEL NUMBER</b>	<b>CCT</b>	<b>DIMENSIONS</b>	<b>WATT</b>	<b>LCP</b>	<b>LUMENS</b>	<b>EFFICACY</b>
CRI	>73.6	EP-VELG2-70	5000K	340x100x495mm	70	70.43	10582	150lm/W
BEAM ANGLE	109.2°	EP-VELG2-100	5000K	340x100x495mm	100	103.64	14988	145lm/W
IP RATING	66	EP-VELG2-150	5000K	340x100x495mm	150	150.43	20581	137lm/W
LIFETIME (L70)	>72,000h	EP-VELG2-200	5000K	380x100x555mm	200	196.81	28491	145lm/W
WARRANTY	5 Years							

